


RESEARCH ARTICLE

WILEY

# Numerical considerations for advection-diffusion problems in cardiovascular hemodynamics

Sabrina R. Lynch<sup>1</sup>  | Nitesh Nama<sup>2</sup> | Zelu Xu<sup>3</sup> | Christopher J. Arthurs<sup>4</sup> | Onkar Sahni<sup>3</sup> | C. Alberto Figueroa<sup>1,2</sup>

<sup>1</sup>Department of Biomedical Engineering, University of Michigan, Ann Arbor, Michigan

<sup>2</sup>Department of Surgery, University of Michigan, Ann Arbor, Michigan

<sup>3</sup>Mechanical, Aerospace and Nuclear Engineering, Rensselaer Polytechnic Institute, New York, New York

<sup>4</sup>School of Biomedical Engineering & Imaging Sciences, King's College London, London, UK

## Correspondence

Sabrina R. Lynch, Department of Biomedical Engineering, University of Michigan, North Campus Research Complex, 2800 Plymouth Road, Ann Arbor, MI 48109.  
Email: srlynch@umich.edu

## Funding information

American Heart Association, Grant/Award Numbers: 18PRE33960252, 20POST35220004; Army Research Office, Grant/Award Number: W911NF-19-C-0094; Edward B. Diethrich M.D. Professorship; National Science Foundation, Grant/Award Numbers: 1531752, 1350454, Graduate Research Fellowships Program (GRFP); Wellcome Trust under Wellcome grant: 204823/Z/16/Z The Centre for Medical Engineering (CME) at King's College London: WT 203148/Z/16/Z

## Abstract

Numerical simulations of cardiovascular mass transport pose significant challenges due to the wide range of Péclet numbers and backflow at Neumann boundaries. In this paper we present and discuss several numerical tools to address these challenges in the context of a stabilized finite element computational framework. To overcome numerical instabilities when backflow occurs at Neumann boundaries, we propose an approach based on the prescription of the total flux. In addition, we introduce a “consistent flux” outflow boundary condition and demonstrate its superior performance over the traditional zero diffusive flux boundary condition. Lastly, we discuss discontinuity capturing (DC) stabilization techniques to address the well-known oscillatory behavior of the solution near the concentration front in advection-dominated flows. We present numerical examples in both idealized and patient-specific geometries to demonstrate the efficacy of the proposed procedures. The three contributions discussed in this paper successfully address commonly found challenges when simulating mass transport processes in cardiovascular flows.

## Novelty Statement

The presented study is to the best of our knowledge the *first* implementation of backflow stabilization for 3D scalar mass transport problems. In addition, this paper is the first analysis of the “consistent flux” boundary condition in 3D patient-specific geometries. The *novelty* of our study is the implementation of backflow stabilization, the consistent flux boundary condition, and discontinuity-capturing stabilization in a unified scalar mass transport framework that can be applied to study the cardiovascular system.

## KEYWORDS

backflow stabilization, cardiovascular simulation, consistent flux boundary condition, discontinuity-capturing operator, Neumann inflow boundary condition, scalar advection diffusion

## 1 | INTRODUCTION

Mass transport of biochemical species plays an important role in numerous cardiovascular pathologies including thrombosis and atherosclerosis. Computational models of mass transport offer the unique capability to study various

biochemical processes essential to understand the kinetics of disease progression, but which are otherwise difficult to measure *in vivo*. However, cardiovascular mass transport problems are characterized by highly advective flows (with Péclet numbers up to  $10^7$ ) that make obtaining an accurate numerical solution challenging. Furthermore, every outlet face of a computational model is an artificial boundary resulting from the arbitrary truncation of a vessel. Therefore, it is necessary to prescribe realistic boundary conditions that result in a stable solution at outlet faces while preserving the accuracy of the solution.

In this work, we present a stabilized finite element framework that incorporates three salient features: (a) a backflow stabilization technique to obtain stable solutions with Neumann outflow boundaries for scalar advection-diffusion problems, (b) a consistent flux boundary condition that minimally disturbs the local physics of the problem on outflow boundaries resulting from the artificial truncation of vessels, and (c) a front-capturing stabilization technique to regularize the solution with a concentration front in scenarios of high Péclet numbers.

**Backflow stabilization:** Neumann conditions have typically been prescribed for outlet boundaries in cardiovascular flows, either through direct imposition of a known traction (ie, zero or constant pressure condition)<sup>1,2</sup> or, more recently, through the coupling of reduced order models (ie, lumped parameter networks) of the distal vasculature, which ultimately results in the specification of a time-varying weak traction on the outlet face.<sup>3</sup> However, Neumann conditions in boundaries exhibiting partial or complete inflow are known to lead to numerical divergence.<sup>4-16</sup> Specifically, prescribing a diffusive flux fails to guarantee stable energy estimates due to the unknown velocity profile at these boundaries.<sup>17</sup> To mitigate these difficulties associated with flow modeling, several strategies have been proposed including adding a backflow stabilization term to the boundary nodes,<sup>7-18</sup> constraining the velocity to be normal to the outlet,<sup>5</sup> or using Lagrange multipliers to constrain the velocity profile at all or some of the outlets.<sup>4</sup> A comparison of these strategies determined that backflow stabilization was the most robust approach with the least impact on both the solution and computational cost.<sup>5</sup>

Similar scenarios of numerical instability can arise in scalar advection-diffusion systems.<sup>19</sup> Despite the numerous reports on backflow stabilization for flow problems<sup>4,5,7-16,20</sup> and 2D heat mass transfer,<sup>21-25</sup> these strategies have not been adopted for 3D cardiovascular scalar advection-diffusion systems. Instead, to circumvent the numerical instability issues in the presence of backflow, mass transport models have resorted to unphysical approaches such as the imposition of arbitrary Dirichlet boundary conditions at the outlet faces,<sup>26,27</sup> artificial extensions of the computational domain<sup>28</sup> that seek to regularize the flow profile, or an artificial increase in the diffusivity of the scalar.<sup>29,30</sup> In this work, we propose a stabilization method for outlet Neumann boundaries, following the ideas presented by Hughes and Wells.<sup>19</sup>

**Consistent flux boundary condition:** While there have been numerous contributions proposing outflow boundary conditions for cardiovascular flow problems,<sup>3</sup> little work has been done for the scalar advection-diffusion problem. Typically, cardiovascular mass transport models have employed either Dirichlet or Neumann conditions prescribing known scalar concentrations<sup>26,27</sup> or diffusive fluxes<sup>31,32</sup> at the outlet face, respectively. An alternative choice of boundary condition, henceforth referred to as “consistent flux boundary condition” has been shown to provide better error estimates.<sup>33</sup> This approach relies on calculating the consistent diffusive flux (rather than imposing an arbitrary diffusive flux) that satisfies the weak form of the mass transport equation. To the best of our knowledge, this boundary condition has been thus far unexplored for cardiovascular mass transport problems. In this work, we demonstrate the superior performance of this approach over the traditional zero diffusive flux boundary condition.

**Front-capturing stabilization techniques:** Another important issue concerning simulation of mass transport in cardiovascular applications is the presence of high Péclet number flows typically found in the large arteries. These advection-dominated flows lead to the development of steep concentration gradients, thereby necessitating the use of stabilization techniques to avoid unphysical oscillations in the numerical solution near the concentration front. To address this issue, several discontinuity capturing methods have been proposed.<sup>34-36</sup> In this work, we discuss the performance of the discontinuity capturing (DC) stabilization technique, implemented in the context of a streamline upwind Petrov-Galerkin (SUPG) stabilized finite element formulation.

Numerical results are presented in both idealized and patient-specific geometries to demonstrate the efficacy of the proposed numerical procedures.

## 2 | METHODS

### 2.1 | Strong form and boundary conditions

The strong form of the governing equation for mass transport in a three-dimensional bounded domain  $\Omega \subset \mathbb{R}^3$  is given as

$$\frac{\partial c}{\partial t} + \mathbf{u} \cdot \nabla c - \nabla \cdot (D \nabla c) = r \quad \text{in } \Omega, \quad (1)$$

where  $c$ ,  $D$ ,  $r$ , and  $t$  denote the concentration of the scalar, diffusion coefficient, source (or reaction) terms and time, respectively and  $\mathbf{u}$  is a known, solenoidal velocity field.  $\Omega$  is an open set with boundary  $\Gamma = \partial\Omega$ , such that:

$$\Gamma = \overline{\Gamma_D \cup \Gamma_N}, \quad (2)$$

$$\Gamma_D \cap \Gamma_N = \emptyset, \quad (3)$$

where  $\Gamma_D$  and  $\Gamma_N$  are the Dirichlet and Neumann partitions of the boundary  $\Gamma$ , respectively.

We consider a further partition of  $\Gamma = \Gamma^{\text{in}} \cup \Gamma^{\text{out}}$ ,  $\Gamma^{\text{in}} \cap \Gamma^{\text{out}} = \emptyset$  such that:

$$\Gamma^{\text{in}}(t) = \{\mathbf{x} \in \Gamma | u_n(\mathbf{x}, t) \leq 0\}, \quad (4)$$

$$\Gamma^{\text{out}}(t) = \Gamma - \Gamma^{\text{in}}(t), \quad (5)$$

where  $u_n$  is the dot product of the velocity with the outward unit normal at the boundary,  $\mathbf{x}$  is the position vector,  $\Gamma^{\text{in}}(t)$  is the inflow boundary, and  $\Gamma^{\text{out}}(t)$  is the outflow boundary.  $\Gamma^{\text{in}}(t)$  and  $\Gamma^{\text{out}}(t)$  are functions of time owing to the time dependence of the velocity field. In this manuscript, the terms “outlet” and “inlet” are used to refer to spatially fixed positions of boundary faces, while the terms “inflow boundary” and “outflow boundary” are used to refer to regions of the boundary that exhibit inflow and outflow at a given time instant, respectively. Given these definitions, a total of four distinct boundaries can be defined for mass transport problems<sup>19</sup>:

$$\Gamma_\beta^\alpha(t) = \Gamma_\beta \cap \Gamma^\alpha(t), \quad \alpha = \{\text{in}, \text{out}\}, \quad \beta = \{D, N\} \quad (6)$$

Typically, finite element simulations of mass transport have considered Dirichlet boundary conditions on inlet faces and Neumann boundary conditions on outlet faces. However, this strategy often shows numerical divergence if back-flow occurs on the Neumann boundary (eg, if  $\Gamma_N^{\text{in}}(t) \neq \emptyset$ ). Indeed, it has been shown that the prescription of diffusive flux on a  $\Gamma_N^{\text{in}}(t)$  boundary fails to guarantee stable energy estimates and therefore leads to numerical divergence.<sup>17</sup> Prescribing the total flux on inflow Neumann boundaries  $\Gamma_N^{\text{in}}(t)$  mitigates this issue, whereas the diffusive flux can be safely prescribed on outflow Neumann boundaries  $\Gamma_N^{\text{out}}(t)$ ,<sup>19</sup> namely:

$$D \nabla c \cdot \mathbf{n} = h^{\text{out}} \quad \text{on } \Gamma_N^{\text{out}}(t), \quad (7)$$

$$-c \mathbf{u} \cdot \mathbf{n} + D \nabla c \cdot \mathbf{n} = h^{\text{in}} \quad \text{on } \Gamma_N^{\text{in}}(t). \quad (8)$$

Here,  $h^{\text{out}}$  and  $h^{\text{in}}$  denote the diffusive and total (ie, advective plus diffusive) flux data, respectively.

## 2.2 | Weak form

The Galerkin weak form for the scalar advection-diffusion problem governed by Equation (1) is as follows: find  $c \in H^1(\Omega)$  such that

$$\int_{\Omega} \left[ \delta_c \frac{\partial c}{\partial t} + \delta_c \mathbf{u} \cdot \nabla c + \nabla \delta_c \cdot D \nabla c \right] dV - \int_{\Gamma_N} \delta_c (D \nabla c) \cdot \mathbf{n} dA = \int_{\Omega} \delta_c r dV \quad \forall \delta_c \in H_0^1(\Omega) \quad (9)$$

where  $\delta_c$  is a weighting function,  $\mathbf{H}^1(\Omega)$  is a (solution) space of once-differentiable functions satisfying the Dirichlet boundary conditions on  $\Gamma_D$ , and  $H_0^1(\Omega)$  is a (weighting) space of once-differentiable functions vanishing on the Dirichlet boundary  $\Gamma_D$ . Since cardiovascular mass transport problems are characterized by high Péclet number flows, we utilize a SUPG stabilized finite element formulation,<sup>37</sup> resulting in the following discrete weak form:

$$\begin{aligned} & \int_{\Omega} \left[ \delta_c \frac{\partial c}{\partial t} + \delta_c \mathbf{u} \cdot \nabla c + \nabla \delta_c \cdot D \nabla c \right] dV - \int_{\Gamma_N} \delta_c (D \nabla c) \cdot \mathbf{n} dA \\ & + \sum_{i=1}^{n_{el}} \int_{\Omega_i} \nabla \delta_c \cdot \mathbf{u} \tau \mathcal{R} dV = \int_{\Omega} \delta_c r dV \quad \forall \delta_c \in H_0^1(\Omega) \end{aligned} \quad (10)$$

where  $n_{el}$  denotes the total number of elements in the discretized domain,  $\Omega_i$  is the domain of the  $i$ -th element,  $\tau$  is the stabilization parameter, and  $\mathcal{R}$  is the residual given as

$$\mathcal{R} = \frac{\partial c}{\partial t} + \mathbf{u} \cdot \nabla c - D \nabla^2 c - r. \quad (11)$$

The stabilization parameter  $\tau$  is given as

$$\tau^{-2} = \tau_1^{-2} + \tau_2^{-2} + \tau_3^{-2}, \quad (12)$$

$$\tau_1^{-2} = \left( \frac{\Delta t}{2} \right)^{-2}, \quad \tau_2^{-2} = \mathbf{u} \cdot \mathbf{g} \mathbf{u}, \quad \tau_3^{-2} = 9D^2 \mathbf{g} : \mathbf{g}, \quad \mathbf{g} = \left( \frac{\partial \xi}{\partial \mathbf{x}} \right)^T \frac{\partial \xi}{\partial \mathbf{x}}, \quad (13)$$

where  $\Delta t$  is the time step size,  $:$  is the Frobenius inner product, and  $\mathbf{g}$  is the metric tensor based on the Jacobian of the mapping between the element coordinates  $\xi$  and the physical coordinates  $\mathbf{x}$  (eg, in 1D,  $g = 4/h^2$ ). We remark that, without loss of generality, the examples shown in this article all use a zero reaction term and hence no contributions from the reaction terms appear in the above-mentioned stabilization terms.

## 2.3 | Backflow stabilization and total flux

Using Equations (7) and (8), the Neumann boundary term in Equation (10) becomes

$$\begin{aligned} \int_{\Gamma_N} \delta_c (D \nabla c) \cdot \mathbf{n} dA &= \int_{\Gamma_N^{\text{out}}(t)} \delta_c (D \nabla c) \cdot \mathbf{n} dA + \int_{\Gamma_N^{\text{in}}(t)} \delta_c (D \nabla c) \cdot \mathbf{n} dA, \\ &= \int_{\Gamma_N^{\text{out}}(t)} \delta_c h^{\text{out}} dA + \int_{\Gamma_N^{\text{in}}(t)} \delta_c (D \nabla c - \mathbf{c} \mathbf{u}) \cdot \mathbf{n} dA + \int_{\Gamma_N^{\text{in}}(t)} \delta_c \mathbf{c} \mathbf{u} \cdot \mathbf{n} dA, \\ &= \int_{\Gamma_N^{\text{out}}(t)} \delta_c h^{\text{out}} dA + \int_{\Gamma_N^{\text{in}}(t)} \delta_c h^{\text{in}} dA + \int_{\Gamma_N^{\text{in}}(t)} \delta_c \mathbf{c} \mathbf{u} \cdot \mathbf{n} dA. \end{aligned} \quad (14)$$

As indicated earlier, diffusive flux Neumann boundary conditions are typically prescribed at outlet faces  $\Gamma_N^{\text{out}}(t)$ . In this scenario, the last term of Equation (14) (ie, advective flux) vanishes since  $\Gamma_N^{\text{in}}(t) = \emptyset$ . However, in cases where  $\Gamma_N^{\text{in}}(t) \neq \emptyset$ , the total flux must be prescribed and therefore the advective flux term in Equation (14) is non-trivial and must be included in Equation (10) to obtain a stable solution. Previous publications on backflow stabilization for

Navier-Stokes problems have introduced a parameter  $\beta$  scaling the advective flux contribution.<sup>5,17,18</sup> However, owing to the lack of mathematical rigor justifying the introduction and choice of such a scaling factor, we do not consider it for the scalar advection-diffusion problem.

## 2.4 | Consistent flux boundary condition

The boundary conditions imposed at artificial boundaries generated due to the truncation of a physical domain form a crucial component of the computational model. Since the downstream physics for mass transport applications is often unknown at such artificial boundaries, the task of identifying appropriate conditions that preserve the accuracy of the solution remains challenging.

While there have been numerous contributions proposing conditions for artificial boundaries in cardiovascular flow problems, little work has been done for the scalar advection-diffusion problem. Typically, cardiovascular mass transport models have employed either Dirichlet or Neumann conditions prescribing scalar concentrations<sup>26,27</sup> or diffusive fluxes<sup>31,32</sup> at the outlet face as in Equation (7), respectively. Neither of these approaches is ideal, since they assume knowledge of a physical quantity which is typically unknown. While imposing an arbitrary Dirichlet outlet boundary condition renders a stable solution, it severely affects the scalar solution field and has resulted in approaches relying on extending the outflow branches to minimize the impact of such conditions in the region of interest.<sup>26,27</sup> These approaches also increase the computational cost due to the larger domain. Conversely, a zero diffusive flux condition has been used more sporadically (likely due to the numerical instabilities associated with backflow, as noted above), and, while seemingly less intrusive than a Dirichlet condition, it still fundamentally prescribes an unknown property on the solution field.

An alternative to this zero diffusive flux condition, proposed in the context of the Navier-Stokes equations by Papanastasiou and Malamataris,<sup>38</sup> is to calculate the diffusive flux that satisfies the weak form of the mass transport equation and iteratively impose it as a boundary condition. This approach amounts to treating the boundary integral in the weak form given by Equation (9) as unknown and is particularly useful when analytic or asymptotic techniques cannot predict the physics downstream from the artificial outlets, making it challenging to formulate appropriate boundary conditions at these faces. The strategy of leaving an undefined boundary integral could lead to an ill-posed variational form, particularly in diffusion-dominated problems which are more elliptical in nature and thus necessitate specification of conditions on every boundary. Conversely, advection-dominated problems have a stronger hyperbolic behavior and are less likely to be affected by the ill-posedness of this strategy. For a more detailed discussion on the mathematical implications of this approach, we refer the reader to the work of Griffiths<sup>33</sup> and Renardy.<sup>39</sup>


In the context of the Navier-Stokes equations, these boundary conditions have been referred to using different terminologies such as “no boundary condition” or “free boundary condition”.<sup>33,38</sup> However, here we will refer to them as “consistent flux boundary condition”. In this work, we employ both the zero diffusive flux (see Equation 7), and the consistent flux boundary conditions for the scalar advection-diffusion problem and compare their performance in preserving the local physics of the computed solution.

## 2.5 | Discontinuity capturing operator

In the context of high Péclet number flows, SUPG stabilized formulations for scalar advection-diffusion problems fail to resolve the steep gradients in the solution, resulting in numerical undershoot/overshoot in concentrations near the scalar front. Therefore, in addition to SUPG stabilization, we implemented a discontinuity capturing (DC) operator to resolve steep gradients in the solution.<sup>40</sup> This approach introduces an additional term for each element of the form  $\nabla \delta_c \cdot \nu_{DC} \nabla c$  in Equation (10) similar to the last term on the LHS.  $\nu_{DC}$  is defined as

$$\nu_{DC} = \max[0, \omega_{DC}] \tilde{\mathbf{g}}, \quad (15)$$

where  $\tilde{\mathbf{g}}$  is the contravariant counterpart of the metric tensor introduced in Equation (13) and



**FIGURE 1** 3D T-shaped bifurcation model


$$\omega_{DC} = f_{DC} \sqrt{\frac{\mathcal{R}^2}{\nabla c \cdot \tilde{\mathbf{g}} \nabla c}} - \tau \frac{\mathcal{R}^2}{\nabla c \cdot \tilde{\mathbf{g}} \nabla c}, \quad (16)$$

where  $f_{DC} = 1$  for linear finite elements and  $\tau$  is the stabilization parameter defined in Equation (12). We want to make two remarks on the DC term: (a) it involves gradients of the weighting function and thus, conservative properties of the semi-discrete form are unchanged,<sup>19</sup> and (b) it makes the weak form of the scalar advection-diffusion problem nonlinear. Therefore, the resolution of gradients near the concentration front is obtained at an increased computational expense. For nonlinear scalar problems, however, the increase in computational cost due to the use of DC operator is not high (as discussed later).

### 3 | NUMERICAL EXAMPLES

In this section, we present numerical results to illustrate the suitability of the proposed computational framework. The following applies to all the numerical examples presented in this section:

- A flow solution is first obtained by solving the stabilized Navier-Stokes equations using the cardiovascular hemodynamics modeling environment, CRIMSON ([www.crimson.software](http://www.crimson.software)).<sup>41</sup> Here, blood is modeled as a Newtonian fluid with a density of 1060 kg/m<sup>3</sup> and a dynamic viscosity of 0.004 Pa · s. All walls are modeled as rigid (ie, homogeneous Dirichlet boundary conditions for the velocity field).
- For all flow solutions backflow stabilization was used when solving the Navier-Stokes equations.
- For the mass transport problems, a constant concentration of  $c = 10 \text{ mol/mm}^3$  is prescribed at the inlet face and a zero diffusive flux boundary condition is applied to all walls. An initial concentration of  $c = 0 \text{ mol/mm}^3$  is assumed for all mass transport problems.



**FIGURE 2** A, Velocity contours in the mid-plane of the T-shaped bifurcation. Red lines indicate velocity profiles at a discrete number of locations. B, Close-up view of the velocity at the outlets, illustrating backflow in a small segment of the outlet face

### 3.1 | Idealized geometries

To provide a better understanding of specific numerical challenges, we first present results for cases where idealized geometries and problem parameters are chosen to isolate specific numerical challenges. Here, we present results for three specific cases that highlight the effectiveness of the different components of the proposed computational framework.

#### 3.1.1 | Backflow stabilization


To illustrate the numerical issues caused by  $\Gamma_N^{\text{in}}(t)$  boundaries, we consider a T-shaped bifurcation as shown in Figure 1. The choice of geometry and boundary conditions for this problem leads to partial backflow at the outlet faces even under steady flow conditions. A velocity field was obtained by prescribing a constant inlet flow of  $196 \text{ mm}^3/\text{s}$ , mapped to a parabolic velocity profile, resulting in a maximum velocity of  $v_{\text{max}} = 2000 \text{ mm/s}$ , a mean velocity of  $v_{\text{mean}} = 1000 \text{ mm/s}$ , and a Reynolds number  $\text{Re}_{\text{mean}} = 66.25$ , based on the mean velocity and the inlet radius. A zero traction boundary condition was applied at both outlet faces. For the scalar advection-diffusion problem, a zero diffusive flux condition was prescribed at the outlet faces. The diffusion coefficient was set to  $D = 10^{-2} \text{ mm}^2/\text{s}$ , resulting in a Péclet number of  $\text{Pe}_{\text{mean}} = 2.5 \times 10^4$ . The domain was discretized using linear tetrahedral elements with characteristic length of  $10^{-2} \text{ mm}$ , resulting in a total mesh size of 11.3 million elements. Simulations were run using a constant time-step size of  $\Delta t = 10^{-5}$  seconds for 8000 time steps.

Figure 2A shows the velocity field plotted at the mid-plane of the T-shaped bifurcation perpendicular to the Z direction. The velocity profiles at the outlet faces exhibit backflow, Figure 2B. Figure 3A shows the solution for the scalar concentration at  $t = 0.036$  seconds, obtained without backflow stabilization. The solution presents strong numerical artifacts on the top outlet boundary, corresponding to the  $\Gamma_N^{\text{in}}(t)$  region of the outlet boundary. These numerical artifacts eventually lead to divergence of the simulation and also appear in the bottom outlet boundary over time. In contrast, the proposed backflow stabilization technique yields a stable solution as shown in Figure 3B. We would like to point out that the two numerical solutions in Figures 3A,B exhibit spurious oscillations in the interior of the domain, these will be addressed in Section 3.1.3

#### 3.1.2 | Consistent flux boundary condition

In this example, we compare the behavior of the consistent flux and the zero diffusive flux boundary conditions. We consider two cylindrical domains of diameter  $d = 1.0 \text{ mm}$  and lengths  $l_1 = 10 \text{ mm}$  and  $l_2 = 5 \text{ mm}$ , respectively.





**FIGURE 3** Scalar contours at time  $t = 0.036$  seconds in the T-bifurcation. A, No backflow stabilization resulting in an unstable solution. B, With backflow stabilization resulting in a stable solution in the presence of backflow

For each cylindrical domain, we apply both types of boundary conditions, rendering a total of four different scenarios. The ultimate goal of this test is to examine the impact of the boundary conditions on the scalar field, specifically by comparing solutions at the outlet of the shorter cylinder with solutions at the mid-section of the longer cylinder, which are taken as the “reference solution.” A desirable feature of a boundary condition is to minimize the impact on the scalar field, given that these conditions are typically prescribed on “artificial” boundaries (ie, arbitrary truncations of a branch).


Steady flow field solutions were obtained by prescribing a constant flow rate of  $196 \text{ mm}^3/\text{s}$ , mapped to a parabolic velocity profile resulting in a maximum velocity of  $v_{\text{max}} = 500 \text{ mm/s}$ , a mean velocity of  $v_{\text{mean}} = 250 \text{ mm/s}$  and a Reynolds number of  $\text{Re}_{\text{mean}} = 33.125$ . A zero traction boundary condition was applied at the outlet face. For the mass transport problem, a constant value of diffusivity was adopted,  $D = 10^2 \text{ mm}^2/\text{s}$ , resulting in Péclet number of  $\text{Pe}_{\text{mean}} = 1.25$ . This relatively low Péclet number was chosen because it amplifies the differences between zero diffusive and consistent flux boundary conditions. Simulations were run using a constant time-step size of  $\Delta t = 10^{-4}$  seconds for 8000 time steps.

Figure 4A shows scalar concentration contours at  $t = 0.042$  seconds. for the long (i-ii) and short (iii-iv) cylinders, respectively. Figure 4B shows scalar concentration profiles at the mid-section of the long cylinder (i-ii) and the outlet face of the short cylinder (iii-iv). For the long cylinder, the solutions overlap each other, indicating that at this location far away from the boundary, and this point in time, there is no noticeable difference between solutions obtained with either boundary condition. For the short cylinder, however, there is a noticeable difference between the solutions obtained with the zero diffusive and consistent flux boundary conditions. Taking the solution in the long cylinder as the “reference solution,” it can be observed that the zero diffusive flux condition renders 10% larger scalar concentration values. In contrast, the consistent flux boundary condition yields scalar values much closer to the true solution, overestimated by just 0.015%. These results illustrate the superior performance of the consistent flux boundary condition in preserving the local physics of the numerical solution near artificial boundaries

### 3.1.3 | Discontinuity capturing operator

Having addressed numerical issues concerning outlet boundaries, we now focus our attention to spurious oscillations in the numerical solution around the concentration front within the computational domain. We consider the flow solution for the shorter cylindrical domain ( $l_2 = 5 \text{ mm}$ ) described in the previous section. A smaller diffusion coefficient  $D = 10^{-2} \text{ mm}^2/\text{s}$  was adopted, resulting in a higher Péclet number of  $\text{Pe} = 1.25 \times 10^4$ , that is of practical interest and exhibits spurious oscillations. A consistent flux boundary condition was prescribed at the outlet face. The same mesh and time step size were used as in the previous section.





**FIGURE 4** A, Scalar contours for four different cylinders. From top to bottom: (i) 10 mm cylinder with the consistent flux outflow boundary condition, (ii) 10 mm cylinder with a zero Neumann outflow boundary condition, (iii) 5 mm cylinder with the consistent flux boundary condition, and (iv) 5 mm cylinder with a zero Neumann boundary condition. B, Line plot showing scalar concentration across the cylinder at  $X = 5 \text{ mm}$  for cases (i) to (iv)

Figure 5A and Figure 5B show concentration contours obtained without and with the DC operator, respectively. Undershoot/overshoot in the numerical solution is apparent near the wavefront of the scalar field when no DC operator is used. These oscillations result in unphysical negative scalar concentrations ( $-0.98 \text{ mol/mm}^3$ ) as well as in values higher than those imposed at the inlet ( $11.92 \text{ mol/mm}^3$ ). Figure 5C shows plots of the scalar concentration along the centerline of the cylinder at different times. It can be observed that spurious oscillations begin in the numerical solution without the DC operator (red line) within the first five time steps ( $t = 0.0005$  seconds) and increase in magnitude with time. In contrast, the use of the DC operator (black line) results in smooth solution profiles for all times

### 3.2 | Patient-specific geometry

Having demonstrated the capabilities of the stabilized computational framework in idealized geometries under steady flows, we now shift our focus to a patient-specific geometry of a human thoracic aortic aneurysm under periodic flow conditions.<sup>42</sup> The aortic geometry was built from computed tomography angiography (CTA) image data using the cardiovascular hemodynamic modeling environment CRIMSON.<sup>41</sup> Figure 6 shows the computational domain comprised of the ascending aorta and nine outlet branches. The aortic geometry was discretized into 6.2 million linear tetrahedral elements and 1.1 million nodes. An echocardiography-derived periodic flow waveform (with time period  $T = 0.91$  seconds) mapped to a parabolic velocity profile was imposed at the aortic inflow, resulting in a maximum Reynolds number of approximately  $\text{Re}_{\max} = 2.1 \times 10^3$ . Three-element Windkessel models<sup>3</sup> were prescribed at each outlet face, representing the behavior of the distal vascular beds (numerical values given in Supporting Information).<sup>42</sup> Cycle-to-cycle periodicity was achieved after running the flow problem under rigid wall assumptions for four cardiac cycles, corresponding to a physical time of  $t = 3.64$  seconds. Subsequently, the scalar advection-diffusion equation was solved, assuming a zero concentration initial condition, a constant Dirichlet inlet boundary condition of  $c = 10 \text{ mol/mm}^3$ , and zero total flux boundary conditions at the vessel walls for  $t > 3.64$  seconds. Simulations were run using a constant time step size of  $\Delta t = 10^{-4}$  seconds.



#### 3.2.1 | Backflow stabilization

We first studied the issue of numerical instabilities on inflow Neumann boundaries ( $\Gamma_N^{\text{in}}$ ). A constant diffusion coefficient,  $D = 1.0 \text{ mm}^2/\text{s}$  was used, resulting in a maximum Péclet number of  $\text{Pe}_{\max} = 8.0 \times 10^3$  at the inlet face.

## (A) No DC Operator



## (B) With DC Operator





**FIGURE 5** A, Scalar contours of 5 mm cylinder without the DC Operator at  $t = 4 \times 10^{-3}$  seconds. B, Scalar contours with the DC Operator at  $t = 4 \times 10^{-3}$  seconds. C, Scalar concentration along the center of the cylinder with and without DC Operator at three instances in time:  $t = 5 \times 10^{-4}$  seconds,  $t = 2 \times 10^{-3}$  seconds and  $t = 4 \times 10^{-3}$  seconds

Zero diffusive flux boundary conditions were prescribed on each outlet face. Figure 7A shows a 3D warp of the velocity profile at the aortic outlet boundary in mid-diastole ( $t = 4.39$  seconds). Flow reversal is apparent on this boundary at this point in time. Using the standard zero diffusive flux boundary condition without backflow stabilization leads to instabilities in the numerical solution and eventual divergence, see Figure 7B. Figure 7C shows the corresponding stable scalar concentration solution obtained with the inclusion of backflow stabilization. There was no significant difference in computational cost between solutions obtained with and without backflow stabilization.

### 3.2.2 | Consistent flux boundary condition

We next studied the performance of the consistent flux vs the zero diffusive flux boundary condition. In both cases, backflow stabilization and a constant value of diffusion coefficient  $D = 10^2 \text{ mm}^2/\text{s}$  were used resulting in a maximum Péclet number of  $Pe_{\max} = 80$  at the inlet face. Figure 8 shows the geometric model with four arbitrary locations A-D along the aorta. Scalar concentration profiles obtained with both boundary conditions at  $t = 6.55$  seconds for locations A-D are given. The concentration profiles show substantial variations along the cross section of the vessel for each location, highlighting the contribution of the advection to the concentration profile. For instance, panels A and B show larger values of concentration along the outer curvature of the aorta, where the velocity field is larger. Panels A and B also show close agreement between the solutions obtained with each boundary condition. In contrast, panels C and D show clear differences between the scalar concentration profiles, with discrepancies between solutions increasing in locations closer to the outlet boundary. Location D shows substantial differences in numerical values and concentration profiles between the two solutions. These results highlight the intrusiveness of the zero diffusive flux boundary condition, particularly in regions of the computational domain near the outlet boundaries. There was no significant difference in computational cost between solutions obtained with the zero diffusive or consistent flux boundary conditions.


**FIGURE 6** A, 3D geometric model reconstructed from CTA image data. B, Computational mesh used in all patient-specific simulations. Both the geometric model and computational mesh were created using CRIMSON




**FIGURE 7** A, Computational domain with thoracic aortic aneurysm showing flow reversal at the descending thoracic aorta outlet. Surface contours of scalar concentration at time  $t = 4.39$  seconds. B, Without scalar backflow stabilization numerical instability is observed at the thoracic aorta outlet that proceeds to pollute the scalar domain. C, With backflow stabilization a stable scalar solution is obtained in the presence of backflow at an outlet

### 3.2.3 | Discontinuity capturing operator

In this last example, we demonstrate the efficacy of the DC operator in resolving spurious oscillations in the scalar concentration solution. A constant diffusion coefficient,  $D = 1.0 \text{ mm}^2/\text{s}$  was used, resulting in a maximum Péclet number of  $Pe_{\max} = 8.0 \times 10^3$  at the inlet face. Consistent flux boundary conditions were prescribed on each outlet face and backflow stabilization was used. Figure 9A,B shows the concentration contours at  $t = 4.04$  seconds obtained without and with the DC operator, respectively. Numerical undershoot/overshoot is observed near the wavefront of the scalar field



**FIGURE 8** Patient-specific simulations in a human thoracic aneurysm were run with both a zero diffusive flux boundary condition (solid red line) and a consistent flux boundary condition (dashed black line). Comparisons of the scalar profile across the diameter of the model are shown at four locations, A to D. Results show that close to the inflow the scalar profile across the aorta is the same for both boundary conditions at outlet faces. After the thoracic aneurysm the scalar profiles begin to differ and the greatest differences are observed near the primary outlet face



**FIGURE 9** Scalar concentration contours at  $t = 4.04$  seconds obtained without, (A), and with the DC operator, (B), respectively. Oscillations in the scalar solution can be seen near the wavefront in (A); a smooth concentration solution can be seen in (B). The lines (in A and B) indicate the location where the scalar concentration profiles are shown in (C). The use of the DC operator effectively avoids the overshoot/undershoot phenomena seen in the simulation with no DC

when no DC operator is used. Figure 9C shows a comparison between the two scalar concentration solutions, plotted along an arbitrary line passing through the concentration wavefront. It can be observed that the solution without the inclusion of the DC operator is characterized by spurious oscillations near the concentration wavefront. These

oscillations result in unphysical (negative) minimum ( $-1.43 \text{ mol/mm}^3$ ) and maximum ( $12.39 \text{ mol/mm}^3$ ) values of concentration. In contrast, the solution obtained with the inclusion of the DC operator shows always positive, smoothly varying scalar concentrations across the wavefront, devoid of any spurious oscillations.

## 4 | DISCUSSION AND CONCLUSIONS

Transport problems are of paramount importance in studying cardiovascular pathologies. Diseases such as intimal hyperplasia, atherosclerosis and thrombosis are all directly affected by complex transient hemodynamics as well as the transport of numerous chemical species and proteins.<sup>43-47</sup> Modeling mass transport in cardiovascular systems presents numerical challenges due to the inherently complex and time-dependent flow patterns and vessel geometries. This complexity is further compounded by the large range of Péclet numbers found in cardiovascular flows. The primary aim of this work is to present a stabilized computational framework to study 3D, transient cardiovascular mass transport problems. This includes the identification of appropriate boundary conditions that allow for physiologic flow reversal as well as use of stabilization techniques to avoid spurious numerical oscillations in the computed concentration field.

A number of previous computational studies have employed modeling assumptions or simplifications that are difficult to justify in cardiovascular mass transport problems. These have included unphysiologically large values of diffusion coefficients to lower the Péclet number<sup>29,30</sup>; unrealistic extension of model branches to regularize velocity profiles near outlet faces<sup>26,27</sup>; and the prescription of arbitrary concentration or flux values at outlet boundaries<sup>26,27</sup> with a significant influence on the computed solution in regions of interest. These simplifications, always resulting from limitations in the numerical approach, severely limit the applicability of such models for general cardiovascular mass transport studies.

The computational framework for cardiovascular mass transport presented in this work has three salient features. Firstly, we have presented a backflow stabilization strategy to obtain stable numerical solutions in the presence of flow reversal at outlet boundaries. Secondly, we have introduced a “consistent flux boundary condition” and have demonstrated its superiority over the typically used zero diffusive flux boundary condition in preserving the local physics of the numerical solution, particularly in cases of low Péclet numbers. Lastly, this framework employs SUPG and DC formulations to resolve steep concentration gradients in mass transport characterized by high Péclet numbers.

We have demonstrated the application of this framework in two different sets of geometries. Firstly, we chose idealized geometries with steady flow conditions to allow for a clear interpretation of different numerical challenges and to illustrate the efficacy of the various stabilization techniques reported in this work. The second set of application examples considered a patient-specific model of a human aortic aneurysm under pulsatile flow conditions. This example illustrates the applicability of the framework to complex cardiovascular mass transport problems.

Figure 3A demonstrates the issue of numerical divergence in simulations with backflow at Neumann boundaries. The problem was set up in such a way that even under steady flow conditions, flow reversal occurred on some fraction of the outlet boundaries ( $\Gamma_N^{\text{in}}$ ). For a diffusion coefficient  $D = 10^{-2} \text{ mm}^2/\text{s}$  and Péclet number of  $\text{Pe}_{\text{mean}} = 2.5 \times 10^4$ , simulations diverged if no backflow stabilization was utilized. Following concepts used for stabilization of outlet boundaries in flow problems, the backflow stabilization condition adds an advective component to the diffusive boundary flux. When running experiments with lower Péclet numbers (ie, with larger diffusion coefficients), stable solutions can be obtained even without any backflow stabilization. This is expected since the contribution of the advective flux to the total flux decreases with smaller Péclet numbers. This observation explains that previous studies could report stable solutions without using stabilized outlet boundary conditions for mass transport problems.<sup>29,30</sup> However, an artificial increase in diffusion coefficient changes the physics of the problem entirely.

In Section 3.1.2, we studied the performance of the “consistent flux” vs standard zero diffusive flux boundary condition in a short cylindrical geometry, and compared the results against reference solutions obtained in an extended cylindrical geometry. Simulations demonstrated the superiority of the consistent flux boundary condition in preserving the local accuracy of the solution near the outlet boundary (Figure 4), albeit a marginal difference relative to the reference truth solution is still noticeable. Important to note, the diffusion coefficient used in this example was increased to  $D = 10^2 \text{ mm}^2/\text{s}$ , leading to a smaller Péclet number of  $\text{Pe}_{\text{mean}} = 10$ . Simulations run with larger Péclet numbers show smaller differences between consistent and zero flux boundary condition results.

In Section 3.1.3, the performance of the DC operator to stabilize oscillations in the wavefront of the scalar field for high Péclet numbers was studied. A diffusion coefficient  $D = 10^{-2} \text{ mm}^2/\text{s}$ , rendering a Péclet number  $\text{Pe} = 10^4$  was considered. Figure 5 illustrates that without the DC operator, overshoot/undershoot in the numerical solution occurs at the



wavefront, resulting in unphysical negative scalar concentrations ( $-0.98 \text{ mol/mm}^3$ ) as well as in concentration values higher than those imposed at the inlet ( $11.92 \text{ mol/mm}^3$ ). The DC operator eliminates the spurious oscillations, rendering a smooth solution without unphysical negative concentrations.

The performance of the three formulations was then tested in a patient-specific aortic aneurysm geometry under pulsatile conditions, see Section 3.2. The backflow stabilization produced stable results in the presence of significant flow reversal (Figure 7). The consistent flux boundary condition showed substantial differences in scalar concentration profiles compared to the zero diffusive flux boundary condition, specifically in regions near the outlet boundary, see Figure 8. Lastly, the DC operator rendered smooth concentration profiles near the wavefront of the solution for high Péclet number transport, see Figure 9.

While the different formulations presented in this work provide a set of robust tools to enable simulation of cardiovascular mass transport under realistic geometries, flow, and Péclet number conditions, further developments are needed. Future work includes validation of the proposed framework with *in vitro* dye perfusion experiments and *in vivo* patient-specific angiography studies. Similarly to the reduced-order models widely adopted for cardiovascular flow problems,<sup>3,48,49</sup> it is critically important to develop reduced-order models of mass transport for the proximal and distal portions of the vascular system not included in the 3D geometric model. This is particularly important when dealing with closed-loop models and simulations involving reaction.

The DC scheme introduces a non-linear term in the weak form of the problem. Although an increase in computational cost was expected, no increase was observed in simulations run with the DC operator. This expense can be mitigated by the use of a time-lagging DC scheme.<sup>50</sup> We remark, however, that in the presence of nonlinearity (eg, in source terms), the scalar advection-diffusion problem would be nonlinear regardless of the DC scheme and computational cost will not be significantly different with and without the DC operator.

## ACKNOWLEDGEMENTS

S.L. is supported by the NSF Graduate Research Fellowship Program and the American Heart Association Fellowship (AHA 18PRE33960252). C.A.F. is supported in part by the Edward B. Diethrich M.D. Professorship. N.N. is supported by the American Heart Association Fellowship (AHA 20POST35220004). C.A. is supported by the Wellcome Trust under Wellcome grant [204823/Z/16/Z], and acknowledges The Centre for Medical Engineering (CME) at King's College London [WT 203148/Z/16/Z]. Z.X. and O.S. gratefully acknowledge the financial support of NSF CAREER grant 1350454 and U.S. Army grant W911NF-19-C-0094. Additionally, computing resources were provided by the NSF via grant No. 1531752 MRI: Acquisition of Conflux.

## ORCID

Sabrina R. Lynch  <https://orcid.org/0000-0002-5220-8861>

## REFERENCES

- Oshima M, Torii R, Kobayashi T, Taniguchi N, Takagi K. Finite element simulation of blood flow in the cerebral artery. *Comput Methods Appl Mech Eng*. 2001;191(6–7):661–671.
- Perktold K, Rappitsch G. Computer simulation of local blood flow and vessel mechanics in a compliant carotid artery bifurcation model. *J Biomech*. 1995;28(7):845–856.
- Vignon-Clementel IE, Figueroa CA, Jansen KE, Taylor CA. Outflow boundary conditions for three-dimensional finite element modeling of blood flow and pressure in arteries. *Comput Methods Appl Mech Eng*. 2006;195(29–32):3776–3796.
- Kim HJ, Figueroa C, Hughes T, Jansen K, Taylor C. Augmented Lagrangian method for constraining the shape of velocity profiles at outlet boundaries for three-dimensional finite element simulations of blood flow. *Comput Methods Appl Mech Eng*. 2009;198(45–46):3551–3566.
- Moghadam ME, Bazilevs Y, Hsia TY, Vignon-Clementel IE, Marsden AL. Others . A comparison of outlet boundary treatments for prevention of backflow divergence with relevance to blood flow simulations. *Comput Mech*. 2011;48(3):277–291.
- Fouchet-Incaux J. Artificial boundaries and formulations for the incompressible Navier-Stokes equations: applications to air and blood flows. *SeMA J*. 2014;64(1):1–40.
- Bruneau CH, Fabrie P. Effective downstream boundary conditions for incompressible Navier-Stokes equations. *Int J Num Method Fluid*. 1994;19(8):693–705.
- Bruneau CH, Fabrie P. New efficient boundary conditions for incompressible Navier-stokes equations: a well-posedness result. *ESAIM Math Model Num Anal*. 1996;30(7):815–840.
- Lanzendörfer M, Stebel J. On pressure boundary conditions for steady flows of incompressible fluids with pressure and shear rate dependent viscosities. *Appl Math*. 2011;56(3):265–285.



10. Feistauer M, Neustupa T. On the existence of a weak solution of viscous incompressible flow past a cascade of profiles with an arbitrarily large inflow. *J Math Fluid Mech.* 2013;15:701-715.
11. Dong S, Karniadakis GE, Chrysosostomidis C. A robust and accurate outflow boundary condition for incompressible flow simulations on severely-truncated unbounded domains. *J Comput Phys.* 2014;261:83-105.
12. Braack M, Mucha PB. Directional do-nothing condition for the Navier-Stokes equations. *J Comput Math.* 2014;32(5):507-521.
13. Porpora A, Zunino P, Vergara C, Piccinelli M. Numerical treatment of boundary conditions to replace lateral branches in hemodynamics. *Int J Num Method Biomed Eng.* 2012;28(12):1165-1183.
14. Dong S, Shen J. A pressure correction scheme for generalized form of energy-stable open boundary conditions for incompressible flows. *J Comput Phys.* 2015;291:254-278.
15. Dong S. A convective-like energy-stable open boundary condition for simulations of incompressible flows. *J Comput Phys.* 2015;302:300-328.
16. Ni N, Yang Z, Dong S. Energy-stable boundary conditions based on a quadratic form: applications to outflow/open-boundary problems in incompressible flows. *J Comput Phys.* 2019;391:179-215.
17. Gravemeier V, Comerford A, Yoshihara L, Ismail M, Wall WA. A novel formulation for Neumann inflow boundary conditions in biomechanics. *Int J Num Method Biomed Eng.* 2012;28(5):560-573.
18. Bertoglio C, Caiazzo A, Bazilevs Y, et al. Benchmark problems for numerical treatment of backflow at open boundaries. *Int J Num Method Biomed Eng.* 2018;34(2):e2918.
19. Hughes TJ, Wells GN. Conservation properties for the Galerkin and stabilised forms of the advection-diffusion and incompressible Navier-Stokes equations. *Comput Methods Appl Mech Eng.* 2005;194(9-11):1141-1159.
20. Bertoglio C, Caiazzo A. A tangential regularization method for backflow stabilization in hemodynamics. *J Comput Phys.* 2014;261:162-171.
21. Pérez CE, Thomas JM, Blancher S, Creff R. The steady Navier-Stokes/energy system with temperature-dependent viscosity-part 1: analysis of the continuous problem. *Int J Num Method Fluid.* 2008;56(1):63-89.
22. Pérez CE, Thomas JM, Blancher S, Creff R. The steady Navier-stokes/energy system with temperature-dependent viscosity-part 2: the discrete problem and numerical experiments. *Int J Num Method Fluid.* 2008;56(1):91-114.
23. Neustupa T. The weak solvability of the steady problem modelling the flow of a viscous incompressible heat-conductive fluid through the profile cascade. *Int J Num Method Heat Fluid Flow.* 2017;27(7):1451-1466.
24. Ceretani AN, Rautenberg CN. The Boussinesq system with mixed non-smooth boundary conditions and do-nothing boundary flow. *Zeitschrift für Angewandte Mathematik Und Physik.* 2019;70.1-24.
25. Liu X, Xie Z, Dong S. On a simple and effective thermal open boundary condition for convective heat transfer problems. *Int J Heat Mass Transf.* 2020;151:119355.
26. Hansen KB, Arzani A, Shadden SC. Finite element modeling of near-wall mass transport in cardiovascular flows. *Int J Num Method Biomed Eng.* 2019;35(1):1-15.
27. Arzani A, Gambaruto AM, Chen G, Shadden SC. Lagrangian wall shear stress structures and near-wall transport in high-Schmidt-number aneurysmal flows. *J Fluid Mech.* 2016;790:158-172.
28. Farghadan A, Arzani A. The combined effect of wall shear stress topology and magnitude on cardiovascular mass transport. *Int J Heat Mass Transf.* 2019;131:252-260.
29. Biasetti J, Spazzini PG, Swedenborg J, Gasser TC. An integrated fluid-chemical model toward modeling the formation of intra-luminal thrombus in abdominal aortic aneurysms. *Front Physiol.* 2012;3:266.
30. Ford MD, Stuhne GR, Nikolov HN, et al. Virtual angiography for visualization and validation of computational models of aneurysm hemodynamics. *IEEE Trans Med Imaging.* 2005;24(12):1586-1592.
31. Leiderman K, Fogelson AL. Grow with the flow: a spatial-temporal model of platelet deposition and blood coagulation under flow. *Math Med Biol.* 2011;28(1):47-84.
32. Yazdani A, Li H, Bersi MR, et al. Data-driven modeling of hemodynamics and its role on thrombus size and shape in aortic dissections. *Sci Rep.* 2018;8(1):2515.
33. Griffiths DF. The 'no boundary condition' outflow boundary condition. *Int J Num Method Fluid.* 1997;24(4):393-411.
34. Hughes TJ, Mallet M. A new finite element formulation for computational fluid dynamics: IV. A discontinuity-capturing operator for multidimensional advective-diffusive systems. *Comput Methods Appl Mech Eng.* 1986;58(3):329-336.
35. Codina R. A discontinuity-capturing crosswind-dissipation for the finite element solution of the convection-diffusion equation. *Comput Methods Appl Mech Eng.* 1993;110(3-4):325-342.
36. De Sampaio P, Coutinho ALGA. A natural derivation of discontinuity capturing operator for convection-diffusion problems. *Comput Methods Appl Mech Eng.* 2001;190(46-47):6291-6308.
37. Brooks AN, Hughes TJ. Streamline upwind/Petrov-Galerkin formulations for convection dominated flows with particular emphasis on the incompressible Navier-Stokes equations. *Comput Methods Appl Mech Eng.* 1982;32(1-3):199-259.
38. Papanastasiou TC, Malamataris N, Ellwood K. A new outflow boundary condition. *Int J Num Method Fluid.* 1992;14(5):587-608.
39. Renardy M. Imposing 'no' boundary condition at outflow: why does it work? *Int J Num Method Fluid.* 1997;24(4):413-417.
40. Le Beau GJ, Ray SE, Aliabadi SK, Tezduyar TE. SUPG finite element computation of compressible flows with the entropy and conservation variables formulations. *Comput Methods Appl Mech Eng.* 1993;104(3):397-422.
41. CRIMSON. www.crimson.software.

42. van Bakel TM, Arthurs CJ, van Herwaarden JA, et al. A computational analysis of different endograft designs for Zone 0 aortic arch repair. *Eur J Cardiothorac Surg*. 2018;54(2):389-396.
43. Hathcock JJ. Flow effects on coagulation and thrombosis. *Arterioscler Thromb Vasc Biol*. 2006;26(8):1729-1737.
44. Tarbell JM. Mass transport in arteries and the localization of atherosclerosis. *Annu Rev Biomed Eng*. 2003;5(1):79-118.
45. Coppola G, Caro C. Arterial geometry, flow pattern, wall shear and mass transport: potential physiological significance. *J Roy Soc Interf*. 2009;6(35):519-528.
46. Kaazempur-Mofrad MR, Wada S, Myers JG, Ethier CR. Mass transport and fluid flow in stenotic arteries: axisymmetric and asymmetric models. *Int J Heat Mass Transf*. 2005;48(21-22):4510-4517.
47. Perktold K, Leuprecht A, Prosi M, et al. Fluid dynamics, wall mechanics, and oxygen transfer in peripheral bypass anastomoses. *Ann Biomed Eng*. 2002;30(4):447-460.
48. Vignon-Clementel I, Figueroa C, Jansen K, Taylor C. Outflow boundary conditions for 3D simulations of non-periodic blood flow and pressure fields in deformable arteries. *Comput Methods Biomech Biomed Engin*. 2010;13(5):625-640.
49. Arthurs CJ, Agarwal P, John AV, Dorfman AL, Grifka RG, Figueroa CA. Reproducing patient-specific hemodynamics in the Blalock-Taussig circulation using a flexible multi-domain simulation framework: applications for optimal shunt design. *Front Pediatr*. 2017; 5:78-78.
50. Catabriga L, Coutinho ALGA. Improving convergence to steady state of implicit SUPG solution of Euler equations. *Commun Num Method Eng*. 2002;18(5):345-353.

## SUPPORTING INFORMATION

Additional supporting information may be found online in the Supporting Information section at the end of this article.

**How to cite this article:** Lynch SR, Nama N, Xu Z, Arthurs CJ, Sahni O, Figueroa CA. Numerical considerations for advection-diffusion problems in cardiovascular hemodynamics. *Int J Numer Meth Biomed Engng*. 2020;36:e3378. <https://doi.org/10.1002/cnm.3378>